

Thermo Scientific Lindberg/Blue M 1500°C General-Purpose Tube Furnaces

Integral temperature control designed for a range of applications which require processing flexibility with fast heatup and recovery



- Energy-efficient Moldatherm insulation increases temperature uniformity, improves energy efficiency and helps to maintain low exterior cabinet temperatures during operation
- Accommodate 1in., 2in. and 3in. O.D. process tubes (customer supplied)
- Silicon carbide heating elements positioned above and below tube works with Type "R" thermocouple to stabilize temperature
- Integral microprocessor-based PID programmable control (proportional, integral, derivative) prevents overshoot
- Adjustable high limit over-temperature protection
- Simultaneous LED display of actual temperature vs. setpoint
- Temperature display in °C or °F

Control options

- B, C
- Optional Over Temperature Control (OTC) available on Multi Program/Multi Segment model (C)
- See page 7 for details

APPLICATIONS

- Heat treatment
- Sintering
- Annealing
- Atmosphere processing
- Melting
- Fusing

Cat. No.	Control	Temperature Range	Heated Zone	Exterior L x W x H	Tube O.D.	Electrical	Shipping Weight	Plug Type
STF55433C-1	B	500° to 1500°C	30.5cm (12in.)	48.3 x 58.4 x 43.2cm (19 x 23 x 17in.)	2.54 to 7.62cm (1 to 3in.)	208/240V 50/60Hz 6000w; 25A	123kg (270 lb.)	no plug, no cable, requires hardwiring
STF55433PC-1	C	500° to 1500°C	30.5cm (12in.)	48.3 x 58.4 x 43.2cm (19 x 23 x 17in.)	2.54 to 7.62cm (1 to 3in.)	208/240V 50/60Hz; 6000w; 25A	123kg (270 lb.)	no plug, no cable, requires hardwiring
STF55433PBC-1	C, OTC	500° to 1500°C	30.5cm (12in.)	48.3 x 58.4 x 43.2cm (19x23x17in.)	2.54 to 7.62cm (1 to 3in.)	208/240V 50/60Hz; 6000w; 25A	123kg (270 lb.)	no plug, no cable, requires hardwiring

To add RS-485 Digital Communications Port to Furnace model, add "COM" before last letter in cat.no. – e.g., STF55433COMC-1

Accessories — Tube Adapters

Cat. No.	Description	For Use with
7100-2444-070	2.5cm (1in.)	STF55433C-1, STF55433PC-1, STF55433PBC-1
7100-2444-068	5cm (2in.)	STF55433C-1, STF55433PC-1, STF55433PBC-1
7100-2444-069	7.6cm (3in.)	STF55433C-1, STF55433PC-1, STF55433PBC-1

Note: Tube adapters sold individually (not as sets).

Ordering information: Required power cord, hardwiring and interconnecting wiring are not included. For information on process tubes contact your process tube supplier
Includes: 1 set of two 2" tube adapters
Warranty*: 1 year (parts and labor)